

# De-Icing Sprayers and Hardware

## 1050 Gallon Basic System De-Icing & Anti-Icing



- High Density Polyethylene Tank
  - Highway Safety Yellow
  - High-Density Polyethylene Resin
  - Max UV Protection and Tank Life
  - 120" long x 65" wide base x 51" high
  - 980 lbs. dry weight, 12,000 lb. wet
  - Full-length steel support under tank
  - Poly Board Equipment platform
  - Honda Industrial Engine GX160
  - Low Oil Alert
  - Banjo 2" Poly Pump 180 GPM Capacity
  - Plumbing System has 2" Suction port for drafting from bulk tank
  - Multi-Port Outlets, 2" and 1" Manual Valved
  - 1" 12 volt remote operated with in cab switch
  - Internal Agitation, Manual Flow Control Bypass
  - Spray Bar with 5 installed flooding nozzles, all quick coupled, spray bar height adjust kit included
-

## 300 Gallon De-Icer Sprayer with 12 Volt, 40 G.P.M. Variable Flow



- 12 Volt powered Spray Unit,
- 300 gallon High-Density Poly Tank,
- Skid Mounted 44" wide x 8-0 long Marine Bronze
- Centrifugal Pump,
- Stainless Steel Shaft,
- 40 G.P.M. capacity with heavier Anti-Icing & De-Icing Liquids
- 12 Volt 60 amp 1/2 hp DC motor
- Vari-speed controls with soft start,
- max amps,
- deceleration,
- Minimum and Maximum speed, adjustable controls.
- In cab mounting control with vari-pot for control of spraying operation. (May require customer supplied 12 volt relay.)

On/off 12 v motorized ball valve, additional 1" manual valve, stainless valve bracket, poly platform, rear bottom loading port. Spray bar included, 90" long, 1 1/2" dia. with 9 ports, 5 installed quick coupled nozzles. Return line for control and self-filling option. DOT Reflective

---

### Available Options:

\*200, 300, 410, 525, 850 & 1050 gallon tanks available

\*Optional hose reels

\*Side spray

\*Right of way spray system

\*Ground speed flow controls